(IC Imtradex

Technical Data

KKM-PTT





Communication system to wear under respiratory mask or protective clothing

- KKM-PTT is a throat microphone with earphone and a large send button
- · connection either to analogue or digital radio sets
- light and comfortable design
- · robust PTT-8 button made of impact-resistant plastic is easy to operate
- 180° turnable cloth clip

Technical data

Send button Housing: impact resistant plastic housing, black, with cloth clip Protection class: IP54 - Protection class: DIN EN 61058-1 VDE 0630 Part 1, EN 60529:1991 DIN VDE 0470-1:1992-11 Life cycle: min. 1.500.000 cycles Microphone Frequency range: 400 Hz – 4 kHz

Pattern: electret Directional: n.n Impedance: 2000 Ohm Sensivity: -41 dB V / Pa, 1 kHz **Speaker** Pattern: dynamic Impedance: 320 Ohm at 1 mW / 1 kHz Sound pressure level: max. 98 dB Frequency range: 300 Hz – 8 kHz Additional Data Temperature range: -20 °C to +70 °C Weight: 160 g

www.imhadex.com

Imtradex Hör-/Sprechsysteme GmbH, Daimlerstraße 23, D-63303 Dreieich, Tel. +49 (0) 6103 48569-40, Fax +49 (0) 6103 48569-60, E-Mail: sales@imtradex.com