

SAVOX

SAVOX C-C550/M7-1 Remote Speaker Mic

The SAVOX C-C550 is a combined remote speaker microphone and body worn push-to-talk unit. It is rugged and has been extensively tested (MIL-STD-810G) to provide robust and reliable communications for professionals working in harsh conditions. The C-C550 is dust tight and submersible in water up to 1m (IP67). The SAVOX C-C550 enables effective remote communications with the radio positioned under clothing and when wearing heavy gloves. Remote activation of the radio's emergency button (radio specific) provides an additional safety feature.

Key Benefits

- Dust proof and water submersible (IP67)
- Extremely rugged design and large PTT buttons
- Excellent tactile feel and operation even with thick gloves
- Exceptional speaker audio performance in noisy and harsh environments
- MIL-STD-810 tested



Market Segment	Public Safety
Size L	79 mm
Size H	115 mm
Housing Colour	Black

Product code	L552132-10B1100
Size W	37 mm
Housing Material	Fibre-Reinforced Plastic
Weight (text)	170 g

Environmental Tests	Blowing Rain MIL810G 506.5, Procedure I, Blowing Sand MIL810G 510.5, Procedure II, Damp heat steady state MIL810G 507.5, Procedure I, Drop MIL810G 516.6, Procedure IV, Dust test MIL810G 510.5, Procedure I, Fluid contamination MIL810G 504.1, Procedure II (occasional contamination), High temperature (operational) MIL810G 502.5, Procedure II, A2, Immersion (IPx7) MIL810G 512.5, Procedure I, Mechanical Shock (Bump) MIL810G 516.6, Procedure I, Mechanical Shock MIL810G 516.6, Procedure I, Salt fog MIL810G 509.5, Solar radiation MIL810G 505.5, Procedure II A2, Thermal shock MIL810G 503.5, Procedure I-A, Vibration MIL810G 514.6, Procedure I, Category 24	Operational Temperature Min	-40 C (-40 F)
Operational Temperature Max	85 C (185 F)	Ingress Protection	IP66, IP67
Storage Temperature Min	-25 C (-13 F)	Storage Temperature Max	70 C (158 F)
Protection Against Drop(fall)	1 meter	RX audio SPL(XXdB; X,X W; X,X m)	90dB/0.5W/0.2m
TX Audio, Microphone Sensitivity(XXdB +/-XdB)	-39dB +/-2dB	Microphone Type	Omnidirectional
Headset Connector	QR4+1 female	Connectivity	Wired
Cable Type	Coiled	Use Voltage	3.0...10.0VDC(0VDC for dynamic microphone)
Emergency Button	No	Attachment/Fastening	Clothing Clip

Compatible Radio Links

Motorola APX4000,
Motorola APX6000,
Motorola APX6000XE,
Motorola APX6500,
Motorola APX7000,
Motorola APX7000L,
Motorola APX7000XE,
Motorola APX7500,
Motorola APX8000,
Motorola DP3400, Motorola
DP3401, Motorola DP3600,
Motorola DP3601, Motorola
DP4400, Motorola DP4401,
Motorola DP4600, Motorola
DP4601, Motorola DP4800,
Motorola DP4801, Motorola
XIRP8200, Motorola
XIRP8208, Motorola
XIRP8260, Motorola
XIRP8268, Motorola
XIRP8660, Motorola
XIRP8668, Motorola
XPR6350, Motorola
XPR6380, Motorola
XPR6550, Motorola
XPR6580, Motorola
XPR7350, Motorola
XPR7380, Motorola
XPR7550, Motorola
XPR7580